

## POS CONCEPT SP-2500 SERIES

THE FREEDOM OF POS SYSTEM DESIGN...



The SP-2500 Series from Partner Tech is a complete new POS concept - no fixed configuration. Customers select their required modules from a large variety of options and it will be configured as a "personalized" POS system. To achieve this high degree of flexibility, the final assembly will take place in Germany.

Each of the modules can be combined with a wide range of peripherals to form a "compact" POS system, or to be used as „stand-alone" to support modular POS design.

By providing an assortment of mounts and fixtures, all thinkable retail installation environments can easily be covered.



Configuration of various monitor sizes



Scan option for operator and customer



Easy serviceable, fast access to HDD/SSD

### SPECIAL FEATURES

- POS system will freely composed by modules
- Powerful Intel® Celeron J1900 (2.00GHz-2.42GHz)
- Monitor size from 11.6" up to 18.5"
- Projected Capacitive Touch (Multi Touch)
- Wide screen format
- VESA standard for all modules

### OPTIONAL

- 7" TFT-LCD customer display (CD-70)
- 3-track MSR (USB interface)
- Smart card/RFID/NFC reader
- Fingerprint sensor or i-Button/Dallas/Addimat2D
- 2D Barcode reader
- Front camera 2.0MP

POS Concept SP-2500 Series

ITEM	SP-2500 TOUCH POS CONCEPT MODULES			
	SP-2500 POS Box-PC	SP-2511 Touch Monitor	SP-2515 Touch Monitor	SP-2518 Touch Monitor
CPU	Intel® Celeron™ J1900 (2.00GHz up to 2.42GHz), quad core, 2MB L2 Cache, fanless			
LCD	-	Bezelfree 11.6" TFT-LCD resolution 1366 x 768 brightness 350cd/m2, LED backlight	Bezelfree 15.6" TFT-LCD resolution 1366 x 768 brightness 350cd/m2, LED backlight	Bezelfree 18.5" TFT-LCD resolution 1366 x 768 brightness 350cd/m2, LED backlight
Touch	-	Projected Capacitive Touch (Multi Touch) with USB interface		
RAM	DDR3 SO-DIMM, 2 slots up to 8GB			
LAN	1 x RJ-45 10/100/1000 BASE-T Gigabit Ethernet			
Storage	1 x 2.5" SATA HDD or SSD (option) / 2nd SATA HDD or SSD (option)			
I/O Interface	4 x COM (DC+0/5/12V: COM 1-2 BIOS selection, COM 3-4 by jumper) 5 x USB 2.0 1 x USB 3.0 1 x RJ-45 Ethernet 1 x RJ-11 Cash drawer control (for 2 cash drawers) 1 x VGA (2nd VGA as option) 1 x DC + 12V Out 1 x Mini PCI-e (internal) 1 x 12V, 1x 24V Powered USB (option) 1 x LPT port or 1 x Audio connector (factory option)			
Speaker	2 x 3W speaker (internal)			
Operating System	Windows 7, POSReady 7, Windows 8.1, Windows 10, Linux (ubuntu)			
Power Supply	AC100~240V/DC+12V, 7.5A, 90W power adaptor, (180W power adaptor in case of Powered USB option)			
Dimensions	240mm (W) x 298mm (D) x 93mm (H) Base only, due to flexible arm, all other dimensions depend on monitor size			
Environment		Operating Temperature 0°C ~ +40°C Humidity 15% ~ 80%	Storage 20°C ~ +60°C -15% ~ 80%	
Options	Powered USB12V/24V, 2nd VGA port, LPT port or Audio connector (factory option)	customer display (CD-70), 3-track MSR (USB I/O), Smart card reader, LF/HF NFC/RFID reader, Fingerprint sensor or i-Button/Dallas//Addimat, 2D Barcode reader, Front camera 2.0MP		
Color	black/silver			

