



CARE . TRUST . RESPONSIBILITY

PT-6212ES, PT-6215ES UND PT-6515BZ PCT

ALL YOU NEED TO BE FLEXIBLE AND INDEPENDENT



The „All-in-One“ POS line PT-6212ES, 6215ES and PT-6515BZ PCT offers a wide range of compact solution for all kind of business.

Due to its compact design, the Partner Tech “All-in-One” Series fits perfectly into environments, where counter space saving and flexibility is demanded. Without extra modules, cables etc. it is easy to install and can be used in many different fields like retail, kiosk, convenience stores, fashion shops or hospitality locations.

SPECIAL FEATURES

- Intel® Celeron J1900 (2.00GHz-2.42GHz, quad core)
- Fanless cooling technology
- Resistive or Projected Capacitive Touch (PT-6515BZ PCT)
- Integrated Epson 80mm thermal printer
- Integrated 3-track MSR
- Modular design for easy maintenance

OPTIONAL

- Mini PCI-e, e.g. to support WLAN module
- Customer display (2x20 VFD or 7")
- IC card/RFID/NFC reader
- Fingerprint sensor or i-Button/Dallas/Addimat


PT-6212ES, PT-6215ES und PT-6515BZ PCT

MODELL	PT-6212ES	PT6215ES	PT-6515BZ PCT
CPU	Intel® Celeron™ J1900 (2.00GHz up to 2.42GHz), quad core, 2MB L2 Cache, fanless		
LCD	12" TFT-LCD resolution 1024 x 768 brightness 350cd/m ² LED backlight	15" TFT-LCD resolution 1024 x 768 brightness 350cd/m ² LED backlight	Bezelfree 15" TFT-LCD resolution 1024 x 768 brightness 350cd/m ² LED backlight
Touch	5-wire resistive ELO touch with USB interface		Projected Capacitive Touch (Multi Touch) with USB interface
RAM	DDR3 SO-DIMM, 2 slots up to 8GB		
Storage	1 x 2.5" SATA HDD or SSD (option)		
LAN	1 x RJ-45 10/100/1000 BASE-T Gigabit Ethernet		
I/O Interface	4 x COM (DC+0/5/12V: COM 1-2 BIOS selection, COM 3-4 by jumper) 3 x USB 2.0 1 x USB 3.0 1 x PS/2 1 x RJ-45 Ethernet 1 x RJ-11 Cash drawer control (for 2 cash drawers) 1 x VGA 1 x LPT (PT-6515BZ PCT only) 1 x Mini PCI-e (internal)		
Speaker	2 x 3W speaker (internal)		
Operating System	Windows 7, POSReady 7, Windows 8.1, Windows 10, Linux (ubuntu)		
Power Supply	AC100~240V/DC+12V, 15A, 180W power adaptor		
Dimensions	328mm (W) x 289.3mm (D) x 246.8mm (H)	345mm (W) x 321mm (D) x 256mm (H)	368mm (W) x 290.5mm (D) x 259mm (H)
Environment	Temperature: Humidity:	Operating: 0°C ~ +40°C 15% ~ 80%	Storage: -20°C ~ +60°C 15% ~ 80%
Integrated Periphery	80mm Epson thermal printer, customer display 2x20 VFD (PT-6212ES/PT-6215ES only), 3-track MSR		
Options	7" or 11.6" monitor on pole, LF/HF NFC/RFID reader, WLAN module, fingerprint sensor, i-Button/Dallas/Addimat 2x20 VFD or CD-70 as customer display (PT-6515BZ PCT)		
Color	black		

*Specification is subject of change without prior notice.



EUROPE	+49 40 450 635-0	info@partner-tech.eu
UNITED KINGDOM	+44 1928 579 707	sales-uk@partner-tech.eu
IBERIA	+34 913 120632	comercial@partner-tech.eu
ADRIA	+386 1 566 25 20	prodaja@partner-tech.eu



Subject to alterations November 2016